



SPECS

TELAIO	
TAGLIE	S,M,L,XL
COLORAZIONI	Blast/Gray/Neon Green
TELAIO	ALUXX SLR-Grade Aluminum
FORCELLA	Composite, ALUXX OverDrive Steerer
COMPONENTISTICA	
MANUBRIO	Giant Contact Low, 31.8mm
ATTACCO MANUBRIO	Giant Contact, 31.8, 8 Degree
TUBOSELLA	Giant D-Fuse, Composite
SELLA	Contact (Neutral)
SISTEMA DI TRASMISSIONE	
LEVE DEL CAMBIO	SRAM GX Trigger
DERAGLIATORE	SRAM X5
CAMBIO	SRAM GX
FRENI	TRP Slate X2
PACCO PIGNONI	SRAM PG1020, 11-36
CATENA	KMC X10 with Missing Link
GUARNITURA	SRAM S1000, 28/42
RUOTE	
DROP MOVIMENTO CENTRALE	SRAM GXP
CERCHI	Giant S-X2 Wheelset, Tubeless
COPERTURE	Giant CrossCut Gravel 2, 700x50Tubeless
EXTRAS	X-D Fender/ ChainStay Protector, Tubeless Upgradeable

CARATTERISTICHE

- ALUXX SLR-grade aluminum frame with D-Fuse composite seatpost
- Giant composite fork with alloy/composite OverDrive hybrid steerer
- SRAM GX 1x10-speed drivetrain
- TRP Slate X2 hydraulic disc brakes
- Giant S-X2 Disc wheelset with Giant CrossCut Gravel 2 tubeless tires
- Color: Blast/Gray/Neon Green



Prezzo: € 1.199

GEOMETRIA

TELAIO	XS	S	M	L	XL
Lunghezza tubo sella (mm)	390	420	460	510	550
Angolo tubo sella	73,0°	73,0°	73,0°	72,0°	71,5°
Lunghezza tubo orizzontale (mm)	580	585	595	605	620
Lunghezza tubo sterzo (mm)	100	125	150	170	190
Angolo sterzo	71,5°	71,5°	71,5°	72,0°	72,0°
Rake forcella (mm)	42	42	42	42	42
Trail (mm)	78	78	78	75	75
Interasse (mm)	1061	1067	1078	1071	1080
Lunghezza carro posteriore (mm)	450	450	450	450	450
Drop movimento centrale (mm)	70	70	70	70	70
Stack (mm)	555	578	602	623	642
Reach (mm)	403	405	408	410	411
Altezza stand over (mm)	696	724	754	795	864
Larghezza manubrio c/c (mm)	640	640	640	690	690
Lunghezza attacco manubrio (mm)	70	70	80	90	100
Larghezza pedivella (mm)	170	170	175	175	175
Dimensione ruote	700C	700C	700C	700C	700C

Le specifiche tecniche e i colori sono soggette a variazioni senza obbligo di preavviso.