

# TRANCE E+ 3 PRO



## SPECS

TELAIO	
TAGLIE	XS, S, M, L, XL
COLORAZIONI	Green/Black
TELAIO	ALUXX SL-grade aluminum, Advanced forged composite upper rocker, 140mm Maestro suspension system
FORCELLA	SR Suntour Aion 35 Air LO-R 27.5+ 150mm travel, Lockout, Boost 110x15mm Quick-Loc thru-axle
AMMORTIZZATORE	Fox Float DPS Performance, EVOL Large Volume sleeve, 3-position lever, 185x52.5mm Trunnion mount, custom tuned
COMPONENTISTICA	
MANUBRIO	Giant Contact SL 35 Trail, 35x800mm
ATTACCO MANUBRIO	Giant Contact SL 35
TUBOSELLA	Giant Contact Switch, dropper, 30,9mm, under bar remote lever
SELLA	Giant Contact, Neutral
SISTEMA DI TRASMISSIONE	
LEVE DEL CAMBIO	Shimano Deore
DERAGLIATORE	MRP 1X CS custom
CAMBIO	Shimano SLX, 10-Speed, Shadow+
FRENI	Tektro HD-M745 Orion, 4-piston, hydraulic disc, 203mm
COMANDI FRENO	Tektro HD-M745 Orion
PACCO PIGNONI	Shimano HG50-10 11-36T, 10-Speed
CATENA	KMC e.10 Turbo, e-bike optimized
GUARNITURA	Praxis Wavetm 36T Cold Forged 4130 premium steel Praxis e-Cadet+ custom forged crankarm set
RUOTE	
CERCHI	Giant AM 27.5+, Tubeless ready, 35mm inner width, e-bike optimized
MOZZI	Giant eTracker Boost, Sealed cartridge bearing, 6-bolt, [F] 110x15 [R] 148x12mm Thru-axle, e-bike optimized
RAGGI	Sapim E-Lite [r] Race [f], e-bike optimized
COPERTURE	Maxxis Minion DHF 27.5x2.6" Foldable, Tubeless, EXO, Dual compound [F] Maxxis Rekon 27.5x2.6" Foldable, Tubeless, EXO, Dual Compound [R]
EXTRAS	Giant EnergyPak 6A Smart charger (60% charge in 60minutes) Tubeless kit
TECNOLOGIA IBRIDA	
MOTORE	Giant SyncDrive Pro, 360% tuneable support, powered by YAMAHA
SENSORS	Giant PedalPlus 4-sensor technology
DISPLAY	Giant RideControl ONE, remote button
BATTERIA	Giant EnergyPak 500, 36V 13.8Ah integrated Lithium-Ion

## CARATTERISTICHE

- Giant SyncDrive Pro, 360% tuneable support, powered by YAMAHA
- Giant EnergyPak500 lithium-ion battery
- SR Suntour Aion 35 LO-R 150mm suspension fork
- Shimano Deore / SLX 10sp speed drivetrain
- Powerful 4-piston hydraulic disc brakes

Prezzo: € 3.999

## GEOMETRIA

TELAIO	S	M	L	XL
Lunghezza tubo sella (mm)	406	445	482	507
Angolo tubo sella	74,0°	74,0°	74,0°	74,0°
Lunghezza tubo orizzontale (mm)	585	610	630	655
Lunghezza tubo sterzo (mm)	95	100	110	130
Angolo sterzo	66,5°	66,5°	66,5°	66,5°
Rake forcella (mm)	46	46	46	46
Trail (mm)	109	109	109	109
Interasse (mm)	1184	1210	1231	1259
Lunghezza carro posteriore (mm)	470	470	470	470
Drop movimento centrale (mm)	15	15	15	15
Stack (mm)	579	584	593	611
Reach (mm)	418	442	460	479
Altezza stand over (mm)	739	740	772	792
Larghezza manubrio c/c (mm)	780	780	780	780
Lunghezza attacco manubrio (mm)	40	50	50	60
Larghezza pedivella (mm)	165	170	170	170
Dimensione ruote	27.5+	27.5+	27.5+	27.5+

Le specifiche tecniche e i colori sono soggette a variazioni senza obbligo di preavviso.